




















Product quality							
Formats		Trendtime 1	Trendtime 2	Trendtime 4	Trendtime 5	Trendtime 6	Trendtime 8
		1285 x 158 x 8 mm	850 x 95 x 8 mm	1285 x 400 x 8 mm	638 x 330 x 8 mm	2200 x 243 x 9 mm	1285 x 330 x 8 mm
Packaging	Pack:	10 Elements	26 Elements	5 Elements	10 Elements	5 Elements	5 Elements
		2.03 m <sup>2</sup> / 15.55 kg	2.1 m <sup>2</sup> / 16.07 kg	2.57 m <sup>2</sup> / 18.93 kg	2.105 m <sup>2</sup> / 15.5 kg	2.673 m <sup>2</sup> / 22.85 kg	2.12 m <sup>2</sup> / 16.55 kg
	Pallet:	45 Pack	30 Pack	28 Pack	40 Pack	39 Pack	34 Pack
		91.364 m <sup>2</sup> / 714.5 kg	62.99 m <sup>2</sup> / 498 kg	71.96 m <sup>2</sup> / 545 kg	84.216 m <sup>2</sup> / 635 kg	104.247 m <sup>2</sup> / 906.15 kg	72.09 m <sup>2</sup> / 577 kg
Guarantee						Notes	
Domestic area:		Lifetime (According Parador guarantee conditions)				- not ready for glue-down	
Commercial area:		5 Years (According Parador guarantee conditions)				- cleaning an maintenance see instructions	
						- technical changes reserved	

Product labelling					Tolerances (EN 13329)		
 EN 14041 : 08							
					Squareness of elements (≤ 0,20 mm)	≤ 0.10 mm	
					Determining the straightness of the edges (≤ 0,30 mm/m)	≤ 0.10 mm/m	
					Height differences of the elements	(average ≤ 0.10 mm)	aver. ≤ 0.05 mm
						(max. ≤ 0.15 mm)	max. ≤ 0.10 mm
					Opening between installed elements	(average ≤ 0.15 mm)	aver. ≤ 0.05 mm
						(max. ≤ 0.20 mm)	max. ≤ 0.10 mm
					Block alignment	± 2 mm	

Classification product features							
		Test standard	Rating			Test standard	Rating
	<b>Utility class 23</b> domestic areas with intensive use	EN 13329	Living room, hall, kitchen, home office		Slip resistance	EN 13893 EN 14041	μ ≥ 0.35 DS
	<b>Utility class 32</b> commercial areas with medium use	EN 13329	Classrooms, small offices, shops		Electrical behaviour	EN 1815	< 2,0 kV antistatic ability
	Abrasion	EN 13329, Annex E	AC 4 (≥ 4.000 revolutions)		<b>Thermal resistance</b> Suitable for installation over underfloor heating when using an appropriate underlay and moisture barrier.	EN 12664	0.048 m <sup>2</sup> *K/W
	Impact resistance	EN 13329, Annex F	IC 2		Effect of a furniture leg	EN 424	No visible changes
	Reaction to fire	EN 13501-1	Cfl s1		Indentation-residual	EN 433	No visible changes
	Staining resistance	EN 438-2	Category 1 + 2: level 5 Category 3: level 4/5		Locking strength of mechanically assembled panels	ISO 24334	-
	Cigarette resistance	EN 438-2	level 4		Acoustical - Impact noise reduction	ISO 717-2	14 dB (with Akustik-Protect 100)
	Light fastness	EN ISO 105 - B02 EN 20105 - A02	Blue wool scale: Stage ≥ 6 Grey scale: Stage ≥ 4		Dimensional stability	ISO 24339	-
	Resistance to roller castor chairs	EN 425	No visible changes		Surface soundness	EN 433	≥ 2.2 N/mm <sup>2</sup>
	Formaldehyde (E1 = 0.1 ppm)	EN 717-1	≤ 0.05 ppm		Slip resistance on an inclined plane	DIN 51130	Depending on structure: -/R 9/R 10
	Thickness swelling	EN 13329, Annex G (≤ 18 %)	≤ 12 %		Disposal	Private waste disposal with normal household waste / bulky waste possible	
	Scratch resistance	EN 438	Level 4				

Changed:	QMB	File:	20161019_PA_TDS_Laminat_Trendtime_EN
Date:	01.01.2014	Updates at:	<a href="http://www.parador.de">www.parador.de</a>
Our technical data sheets are constantly updated and adapted to the latest technology. This version replaces all earlier versions and is valid from:			19.10.2016